8	7		6
Performance Parameters	Symbol	Unit	AVM40-HF-6.4
Stroke	S	mm	6.4
Continuous Force @100°C <sup>[1][2]</sup>	Fc	Ν	17.7
Peak Force <sup>[2]</sup>	F <sub>pk</sub>	N	96.3
Force Constant ±10% <sup>[2]</sup>	K <sub>f</sub>	N/A	13.6
Back EMF Constant ±10% <sup>[2]</sup>	K <sub>e</sub>	V/(m/s)	13.6
Motor Constant @25°C <sup>[2]</sup>	K <sub>m</sub>	N/Sqrt(W)	5.82
Resistance @25°C ±10% <sup>[3]</sup>	R <sub>25</sub>	Ω	5.48
Inductance ±20% <sup>[4]</sup>	L	mН	1.44
Electrical Time Constant	Te	ms	0.26
Continuous Current @100°C <sup>[1]</sup>	I <sub>c</sub>	А	1.3
Peak Current	I <sub>pk</sub>	А	7.0
Continuous Power Dissipation @100°C	<sup>[1]</sup> P <sub>c</sub>	W	11.9
Max. Coil Temperature	t <sub>max</sub>	°C	100
Thermal Dissipation Constant <sup>[1]</sup>	K <sub>th</sub>	W/°C	0.159
Max. Voltage	U <sub>max</sub>	Vdc	60
Coil Mass	m <sub>coil</sub>	g	49.0
Core Mass	m <sub>core</sub>	g	195.0
Running Clearance	Lgap	mm	0.50

thermal environment.



